

Syracuse

glue-down luxury vinyl flooring
for residential use



WARRANTY • 20 YEARS RESIDENTIAL
| 10 YEARS COMMERCIAL

DIMENSIONS

Length & Width	9" X 56"
Gauge	0.12"/ 3 mil
Wear Layer	20 mil/0.5 mm
Per box:	31.50 sq ft / 36.38 lbs

SPECIFICATIONS | ASTM 1700, SOLID VINYL TILE

	STANDARD	RESULT
Critical Radiant Flux	ASTM E648	Class 1
Smoke Density	ASTM E662	≤ 450
Short Term Residual Indentation	ASTM F1914	Exceeds
Flexibility	ASTM F-137	Passes 24 mm mandrel
Thickness	ASTM F-381	Exceeds
Dimensional Stability	ASTM F2199	TBD
Resistance to Chemicals	ASTM F-925	Meets or exceeds
Heat Stability	ASTM F-1514	< 8.0 Δ E
Light Stability	ASTM F-1515	< 8.0 Δ E
Size & Squareness	ASTM F-2421	Exceeds

BELLE GROVE | GM-1501




LORRY RANCH | GM-1502



ROSECLIFF | GM-1503



LYNDHURST | GM-1504



BELLE MEADE | GM-1505



EMLIN | GM-1506



BLOOMFIELD | GM-1507



HILLEROD | GM-1508

