

American Experience & American Journey

SPECIFICATIONS:	PRODUCT NAME:	Engineered 3/8"		
	THICKNESS:	3/8"	WIDTH:	3" (Oak Only) and 5"
	FINISH APPEARANCE:	Satin	FINISH / WARRANTY:	Aluminum Oxide Finish, 25 year finish warranty
	WEAR LAYER:	1/12" (2mm) Hardwood Top Layer	EDGE TREATMENT:	Micro-beveled sides and ends
	TREATMENT:	Smooth Face	RADIANT HEAT:	Oak Only
	INSTALL METHOD:	Float, Glue or Nail/Staple	STRUCTURAL:	Lifetime Residential
	WOOD SPECIES:	Oak and Hickory	JANKA HARDNESS:	Oak: 1290 ; Hickory:1450
	SUBFLOORS:	5/8" or 3/4" Plywood, 3/4" OSB (Oriented Strand Board), Concrete	REFINISHING :	Can be "screened and recoated" (unlimited) due to excessive wear or "sanded and refinished" (1 time) due to damage to a large area if required by a professional refinisher.
	CONSTRUCTION:	5- Ply Cross Directional Construction For Maximum Dimensional Stability		

PRODUCTS:	SPECIES	WIDTH	COLOR	ITEM #	Treatment	SF Per Carton	Cartons Pallet	Truckload QTY	Carton Weight	Pallet Weight
	Red Oak	3"	Natural	CL3000	Smooth	29.5	28	32	42 Lbs.	1,185 lbs.
	Red Oak	3"	Café	CL3003	Smooth	29.5	28	32	42 Lbs.	1,185 lbs.
	Red Oak	3"	Gunstock	CL3002	Smooth	29.5	28	32	42 Lbs.	1,185 lbs.
	Red Oak	3"	Butterscotch	CL3001	Smooth	29.5	28	32	42 Lbs.	1,185 lbs.
	Red Oak	5"	Natural	CL5000	Smooth	34	28	32	48 Lbs.	1344 lbs.
	Red Oak	5"	Café	CL5003	Smooth	34	28	32	48 Lbs.	1344 lbs.
	Red Oak	5"	Gunstock	CL5002	Smooth	34	28	32	48 Lbs.	1344 lbs.
	Red Oak	5"	Butterscotch	CL5001	Smooth	34	28	32	48 Lbs.	1344 lbs.
	Vintage Hickory	5"	Natural	CL5200	Smooth	34	28	32	48 Lbs.	1344 lbs.
	Vintage Hickory	5"	Ginger	CL5201	Smooth	34	28	32	48 Lbs.	1344 lbs.
	Vintage Hickory	5"	Graphite	CL5203	Smooth	34	28	32	48 Lbs.	1344 lbs.

PRODUCT FEATURES:	•	Proudly hand-crafted in the United States of America.
	•	Over 115 years of hardwood manufacturing experience.
	•	All timber is harvested from sustainable U.S. Forests.
	•	Engineered products exceed requirements of the CARB emission standards for indoor air quality.
	•	This collection includes a standard tongue and groove system, which is convenient for multiple installation methods.
	•	Easy maintenance! Sweep and vacuum before any approved wet cleaners are used (Bona Kemi). It is also recommended to place walk off mats in major traffic areas (i.e. front door, near kitchen sink etc.)
	•	NOTE: If floating installation method is used, TONGUE AND GROOVE glue is required for this installation.

--	--