



Construction									
Type	Urban Loft								
Widths	7 1/2" (189 mm)								
Length - Multi-Lengths	Majority 74" (majority 1,880 mm)								
Edges	Micro-V on all 4 sides								
Joint	Tongue and groove								
Thickness	<table border="0"> <tr> <td><b>Total</b></td> <td><b>0.59" (15 mm)</b></td> </tr> <tr> <td><b>Wear Layer</b></td> <td>5/32" (4 mm) Dry solid sawn</td> </tr> <tr> <td><b>Core:</b></td> <td>0.35" (9 mm) Canadian lumber</td> </tr> <tr> <td><b>Balancing base layer:</b></td> <td>0.08" (2 mm) Poplar Veneer</td> </tr> </table>	<b>Total</b>	<b>0.59" (15 mm)</b>	<b>Wear Layer</b>	5/32" (4 mm) Dry solid sawn	<b>Core:</b>	0.35" (9 mm) Canadian lumber	<b>Balancing base layer:</b>	0.08" (2 mm) Poplar Veneer
<b>Total</b>	<b>0.59" (15 mm)</b>								
<b>Wear Layer</b>	5/32" (4 mm) Dry solid sawn								
<b>Core:</b>	0.35" (9 mm) Canadian lumber								
<b>Balancing base layer:</b>	0.08" (2 mm) Poplar Veneer								
Relative Humidity	35% - 65%								
Fabrication	Designed in Canada (Quebec). (Imported product)								

Products	
Series	Urban Loft
Species	White Oak
Grade	<b>Character:</b> Pronounced color variations and wood natural characteristics, such as sound knots of all lengths, open knots of less than 5/64" (2 mm) and knots filled with putty, mineral streaks, surface checks, splits and a few others.
Style	Character
Texture	Wire Brushed
Sheen (Gloss Level)	Ultra-matte (10%)
Colors	Alcove, Brooklyn, Chelsea Cream, Cité, Exposed Oak, Factory, Fifth Avenue, Old York, Park Avenue, Tribeca

Finish																	
Titanium™ Finish	Polymerized titanium finish enhanced with nanotechnology																
Characteristics	<table border="0"> <tr> <td><b>Appearance:</b></td> <td>Superior</td> <td><b>Durability:</b></td> <td>Superior</td> </tr> <tr> <td><b>Gloss losing resistance:</b></td> <td>Superior</td> <td><b>Stain Resistance:</b></td> <td>Superior</td> </tr> <tr> <td><b>Easy to maintain:</b></td> <td>Superior</td> <td><b>Easy to repair:</b></td> <td>Superior</td> </tr> <tr> <td><b>Solvent &amp; Water:</b></td> <td>Free</td> <td><b>Formaldehyde:</b></td> <td>Free</td> </tr> </table>	<b>Appearance:</b>	Superior	<b>Durability:</b>	Superior	<b>Gloss losing resistance:</b>	Superior	<b>Stain Resistance:</b>	Superior	<b>Easy to maintain:</b>	Superior	<b>Easy to repair:</b>	Superior	<b>Solvent &amp; Water:</b>	Free	<b>Formaldehyde:</b>	Free
<b>Appearance:</b>	Superior	<b>Durability:</b>	Superior														
<b>Gloss losing resistance:</b>	Superior	<b>Stain Resistance:</b>	Superior														
<b>Easy to maintain:</b>	Superior	<b>Easy to repair:</b>	Superior														
<b>Solvent &amp; Water:</b>	Free	<b>Formaldehyde:</b>	Free														
Static Friction Coefficient ASTM D-2394-99	Slippery resistance coefficient more than 0.5																

Installation, Usage, Warranties & Accessories																	
Installation	<table border="0"> <tr> <td><b>Levels:</b></td> <td>Basement, main and upper floors</td> <td><b>Methods:</b></td> <td>Nailed, stapled, glued or floated</td> </tr> <tr> <td><b>Subfloors:</b></td> <td colspan="3">Ceramic, vinyl, concrete, plywood or OSB 3/4"</td> </tr> </table>	<b>Levels:</b>	Basement, main and upper floors	<b>Methods:</b>	Nailed, stapled, glued or floated	<b>Subfloors:</b>	Ceramic, vinyl, concrete, plywood or OSB 3/4"										
<b>Levels:</b>	Basement, main and upper floors	<b>Methods:</b>	Nailed, stapled, glued or floated														
<b>Subfloors:</b>	Ceramic, vinyl, concrete, plywood or OSB 3/4"																
Radiant Heat	Compatible																
Maintenance	Recommended hardwood flooring cleaning products																
Uses	Residential & light commercial																
Warranties	<table border="0"> <tr> <td><b>Structural:</b></td> <td>Lifetime</td> </tr> <tr> <td><b>Finish wear-through:</b></td> <td>Residential: 35 years      Light Commercial: 5 years</td> </tr> </table>	<b>Structural:</b>	Lifetime	<b>Finish wear-through:</b>	Residential: 35 years      Light Commercial: 5 years												
<b>Structural:</b>	Lifetime																
<b>Finish wear-through:</b>	Residential: 35 years      Light Commercial: 5 years																
Available Moldings	<table border="0"> <tr> <td><b>Round Stair Nosing*:</b></td> <td>84" L x 3 1/8" W x 0.59" H (2,133 mm L x 79 mm W x 15 mm H)</td> <td><b>Reducer*:</b></td> <td>84" L x 3 1/8" W x 0.59" H (2,133 mm L x 79 mm W x 15 mm H)</td> </tr> <tr> <td><b>Square Stair Nosing*:</b></td> <td>84" L x 4 1/4" W x 0.59" H (2,133 mm L x 108 mm W x 15 mm H)</td> <td><b>Quarter Round:</b></td> <td>84" L x 3/4" W x 3/4" H (2,133 mm L x 19 mm W x 19 mm H)</td> </tr> <tr> <td><b>T-Molding:</b></td> <td>84" L x 2" W x 3/4" H (2,133 mm L x 50.8 mm W x 19 mm H)</td> <td colspan="2"><i>*Only stair nosings and reducers reproduce the texture of the hardwood floor. Please refer to our Molding Guide for more information.</i></td> </tr> <tr> <td><b>Threshold:</b></td> <td>84" L x 2 1/8" W x 3/4" H (2,133 mm L x 53.98 mm W x 19 mm H)</td> <td colspan="2"></td> </tr> </table>	<b>Round Stair Nosing*:</b>	84" L x 3 1/8" W x 0.59" H (2,133 mm L x 79 mm W x 15 mm H)	<b>Reducer*:</b>	84" L x 3 1/8" W x 0.59" H (2,133 mm L x 79 mm W x 15 mm H)	<b>Square Stair Nosing*:</b>	84" L x 4 1/4" W x 0.59" H (2,133 mm L x 108 mm W x 15 mm H)	<b>Quarter Round:</b>	84" L x 3/4" W x 3/4" H (2,133 mm L x 19 mm W x 19 mm H)	<b>T-Molding:</b>	84" L x 2" W x 3/4" H (2,133 mm L x 50.8 mm W x 19 mm H)	<i>*Only stair nosings and reducers reproduce the texture of the hardwood floor. Please refer to our Molding Guide for more information.</i>		<b>Threshold:</b>	84" L x 2 1/8" W x 3/4" H (2,133 mm L x 53.98 mm W x 19 mm H)		
<b>Round Stair Nosing*:</b>	84" L x 3 1/8" W x 0.59" H (2,133 mm L x 79 mm W x 15 mm H)	<b>Reducer*:</b>	84" L x 3 1/8" W x 0.59" H (2,133 mm L x 79 mm W x 15 mm H)														
<b>Square Stair Nosing*:</b>	84" L x 4 1/4" W x 0.59" H (2,133 mm L x 108 mm W x 15 mm H)	<b>Quarter Round:</b>	84" L x 3/4" W x 3/4" H (2,133 mm L x 19 mm W x 19 mm H)														
<b>T-Molding:</b>	84" L x 2" W x 3/4" H (2,133 mm L x 50.8 mm W x 19 mm H)	<i>*Only stair nosings and reducers reproduce the texture of the hardwood floor. Please refer to our Molding Guide for more information.</i>															
<b>Threshold:</b>	84" L x 2 1/8" W x 3/4" H (2,133 mm L x 53.98 mm W x 19 mm H)																

Product standards	
Formaldehyde Emission ASTM D6007-14	Below limit of quantitation of 0.008 ppm
VOC Total ASTM-D-6670-01	0.003 ppm (depends on wood species)
Surface Burning ASTM-E84	Classe 3 or C
R Value	R 0.44 to 0.51 (depends on wood species)
Critical Radiant Flux ASTM-E-648-94a	0.25 - 0.40 watt/cm <sup>2</sup> (depends on wood species)

Certifications	
CARB 93120 Phase II	Compliant
Lacey Act	Compliant

Packaging	
Coverage per box	22.7 ft <sup>2</sup> (2.11 m <sup>2</sup> )
Box size	74 13/32" L x 7 9/16" W x 3 25/32" H (1,890 mm L x 192 mm W x 96 mm H)
Box weight	42 lbs
Boxes per pallet	35
Coverage per pallet	794.5 ft <sup>2</sup> (73.81 m <sup>2</sup> )
Pallet size	75 33/64" L x 28 3/4" W x 37 51/64" H (1,918.1 mm L x 730.25 mm W x 960 mm H)

Relative Species Hardness	
NWFA Janka	White Oak: 1,360 lbs - 5% harder
Hardness Test (ASTM-D-143)	
Red Oak 1290 lbs* - 100%      *lbs = Applied force in pounds	